Product data sheet Grinding quality



R 996



Features:

i cutui coi	
Grain:	Ceramic grain
Backing:	Y-cloth, waterproof
Bonding:	Artificial Resin
Coating:	Closed
Additions:	Top-Size coating
Grit Range:	36, 40, 50, 60, 80 *
Appearance:	Branded
	* = in stock = available within 3-5 weeks

Benefits:

- Extremely strong stock removal
- Constantly strong stock removal
- Extremely long operation life
- Extremely cool grinding
- Maximum performance
- Cost reduction per workpiece
- Low heat development
- Improvement of the work processes
- Less effort and lower energy consumption

For the right cutting speed for your application, please refer to the cutting speed information sheet.

GeBrax GmbH

Obere Hommeswiese 41–45 57258 Freudenberg Germany

Phone: +49 27 34 / 28 474-0 Fax: +49 27 34 / 28 474-10

E-Mail: info@gebrax.de www.gebrax-abrasives.com

Further information on request. Subject to technical changes.

Applications:

- Has been especially developed for the most-demanding applications
- Precision castings (stainless steel, cobalt-chrome)
- For the aviation industry, cast houses
- Medical prosthetics (cast)
- Forgings (tools, turbine blades
- Rolling mills (grinding of metal sheets)
- General engineered operations (high chipping requirements)

Application example:



Materials:

