

SCD surface conditioning discs 3M SC-DH



Features:

| | | |
|-------------|---|-----------------|
| Grain: | Non-woven (red): | Aluminum oxide |
| | Non-woven (black): | Silicon Carbide |
| Mounting: | Velcro (no velour) | |
| Grit Range: | A-Coarse, A-Medium, A-Very Fine, S-Super Fine | |
| Appearance: | Branded | |

Benefits:

- Open structure avoids clogging for a longer service life
- Cool cut
- Adaptable disc for preparing surfaces

Applications:

- Reducing roughness
- Removal of tarnishing
- Smoothing surfaces
- Cleaning, deburring and finishing work
- Suitable for metal, composites, plastic and other materials
- Very good on stainless steel

| ∅ | Mounting | max. rpm |
|--------|------------|--------------|
| 115 mm | (x 22 mm) | 6000 (8.000) |

For the right cutting speed for your application, please refer to the cutting speed information sheet.

Application example:



GeBrax GmbH

Obere Hommeswiese 41-45
57258 Freudenberg
Germany

Phone: +49 27 34 / 28 474-0
Fax: +49 27 34 / 28 474-10

E-Mail: info@gebrax.de
www.gebrax-abrasives.com

Further information on request. Subject to technical changes.

Materials:

