

## Roloc non-woven combi discs GB 633



### Features:

Grain:	Non-woven: Aluminum oxide / cloth: ceramic grain
Intake:	Roloc quick change system
Grit Range:	A-Medium / P 80
Appearance:	Neutral


### Benefits:

- Enormous saving of time and abrasives
- Reduction of work steps
- Achieving of a grain 240 grinded surface

### Applications:

- The Roloc non-woven combi discs GB633 provides the unique application advantage to grind down stainless steel material TIC weld seams with discolorations and at the same time receive a polished surface (with grinding pattern).
- This results in an enormous saving of time and abrasives compared to traditional processes, because two work steps can be left out.
- The surface finish of the disc achieves approx. 90% of the quality that is achieved with traditional abrasives in three work steps.

Application examples:



Ø	Intake	max. rpm
76 mm	Roloc	20.000

For the right cutting speed for your application, please refer to the cutting speed information sheet.

### GeBrax GmbH

Obere Hommeswiese 41–45  
57258 Freudenberg  
Germany

Phone: +49 27 34 / 28 474-0  
Fax: +49 27 34 / 28 474-10

E-Mail: [info@gebrax.de](mailto:info@gebrax.de)  
[www.gebrax-abrasives.com](http://www.gebrax-abrasives.com)

Further information on request. Subject to technical changes.

### Materials:

