

Spiral belts 3M™ 237 AA Trizact™



Features:

Grain:	Aluminum oxide
Backing:	X-cloth, coiled design
Bonding:	Artificial Resin
Coating:	Mikroreplication
Additions:	Additives, 3D pyramid structure
Grit Range:	A160, A100, A80, A65, A45, A30, A16, A6

Benefits:

- Strong stock removal with consistent surface quality
- Low grinding pressure required
- Reduction of grinding steps up to the fine grinding
- Long operation life
- Cool grinding and excellent surface

Ø in mm	max. rpm
10	38.000
13	30.000
15	26.000
19	19.000
22	17.000
25	15.000
30	13.000
45	8.500
60	6.500
75	5.000
100	4.000

For the right cutting speed for your application, please refer to the cutting speed information sheet.

Applications:

- For hard metal surfaces like stainless steel, nickel, titanium, cobalt and chrome
- For the fine grinding of workpieces, like e.g. implants, dental or medical devices, golf clubs, turbine blades, sporting arms, cutlery, stainless steel pots saucepans and fittings

Application examples:



GeBrax GmbH

Obere Hommeswiese 41-45
57258 Freudenberg
Germany

Phone: +49 27 34 / 28 474-0
Fax: +49 27 34 / 28 474-10

E-Mail: info@gebrax.de
www.gebrax-abrasives.com

Further information on request. Subject to technical changes.

Materials:

